
DATA SHEET GROUND COVER

TECHNICAL SPECIFICATIONS





APGE STOCKS FOR FAST DELIVERY

ENPILON GROUND COVER

A THE PARTY OF THE	THE PARTY OF THE P	AL HOUSE, OR HIS EXCESS VI. TO THE THE THE TOTAL THE THE
Construction	1100	1300
Tape composition	Polypropylene	Polypropylene
Colour	Black / white	Black
Weight	110 gr/m² (+/- 3%)	130 gr/m² (+/- 3%)
Yarns per 10 cm / warp	94	112
Yarns per 10 cm / weft	45	56
	Name of the Party	THE REAL PROPERTY OF THE PARTY
UV guarantee	1100	1300
Black	5 years in Central Europe	5 years in Central Europe
White	4 years in Central Europe	4 years in Central Europe
ALL AREAST TOTAL TOTAL CONTROL OF THE	L. BYTE WAS A SHOW THE PARTY OF	
Mechanical properties	1100	1300
Tear resistance kN / 5 cm	20/14 EN-ISO 10319	21/21 EN-ISO 10319
Elongation at break warp %	13/12 EN-ISO 10319	13/12 EN-ISO 10319
Shrink %	0	0
Puncture resistance N	2100 EN-ISO 12236	3000 EN-ISO 12236
	to B. S. Land and St. Company	We will be a second of the sec
Green marking	1100	1300
	Green squares 25 cm	Green lines 25 cm
アンドラ かんりゅう アードン	THE RESERVE AND ASSESSMENT OF THE PARTY OF T	A STATE OF THE PARTY OF THE PAR
Water permeability	1100	1300
	20 / liter / m² / second – EN-ISO 11058	20 / liter / m² / second – EN-ISO 11058

- PROFESSIONAL GROUND COVER
- UV STABILIZED
- AVAILABLE IN VARIOUS GRAMMAGES, WIDTHS AND ROLL LENGTHS

